



— LEADING THE WAY —

EMBLEM Solvent Frontlit Banner 510 SM FR

EMBLEM SOFB510SMFR is a versatile PVC frontlit banner. It conforms to Fire Protection Class B1 and may therefore be used both indoors and outdoors. The semimatt white surface supports excellent printing results.

Matchcode:	SOFB510SMFR
Material:	PVC coated scrim
Finish:	semimatt
Color:	white
Weight:	510 g/m ²
Breaking strength:	2200 / 1900 N/5 cm DIN 53352
Tear strength:	300 / 250 N acc. DIN 53352
Flame retardant:	acc. to DIN 4102-B1
Standard roll width:	110 cm, 54", 60", 63"
Standard roll length:	25 m - additional 104", 126" in 50 m
Temperature resistance:	-20 to 70°C

COMPATIBLE INKS:

Eco solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-9950 · Telefax: +49 41 93-995220
E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Solvent Frontlit Banner 510 SM FR

Description:

Results of our test with SOFB510SMFR have been positive with good print quality using solvent, eco solvent, UVC and latex inks.

The main field of application for this material is the production of promotion banners for short and medium term outdoor advertisements.

Processing:

The material can be eyed, welded, is stickable and sewable. It is necessary that eyes are placed in a distance which is proportionated to the expected wind load and own weight of the banner.

Please take care that the banner is fixed at the full width onto the core caused for technical reasons.

Application:

Main fields of application are indoor/outdoor promotional messages